

DYNACON USS class devices

DNC 40xx series



USS – Unified Security Servers - DYNACON switches. Built to transform your network into a hybrid, complementary communications system with full protection and monitoring.

The 40xx platform is part of the 4xxx family. It is modular and allows you to use flexible and high-performance access and uplink connections in your network - 100 Gb/s, 40 Gb/s, 25 Gb/s, 10 Gb/s, multigigabit and 1 Gb/s.



The most important features of the platform

- High performance based on fast x86 Intel Xeon processors, large RAM memory (32 GB installed by default) and efficient Intel controllers allow for flexible and stable network operation.
- Modular design with the possibility of installation, in addition to communication ports, specialized functions, including LTE terminals, additional storage, hardware modules supporting image and video analytics.
- Industrial modules available with support for IEEE 1588 v1 and v2 PTP/802.1AS.
- Firewall operating at layers 3 and 2, allowing for the extension of industrial security to non-IP-based traffic.
- Dynacon IDCS-AIN, a modern enterprise operating system with support for programmability, application hosting, telemetry. The system is equipped with a full range of switch, router, ZBFW, IPS/IDS, monitoring and security configuration options, bringing a new quality to enterprises.
- Equipping the platform with the ARTEMIDA extraction, inspection and monitoring subsystem. It ensures that there is no need to use additional monitoring devices. The 40xx platform simultaneously works as active network devices and at the same time ensures network security and monitoring. Integration with XDR, EDR, IDS, SIEM, SOAR class master systems brings the platform to a higher level of flexibility and network security architecture.
- Additional space for a replaceable module. Possibility of building the platform with up to 25 communication ports (e.g. 15 x RJ 45, 8 x 10 Gb/s, 2 x 10 Gb/s)
- Additional space for an expansion card.

The implementation of high-performance IPSec, also in the DMVPN implementation, allows for flexible and efficient creation of communication tunnels while ensuring security, which is provided by the latest encryption algorithms, including AES-256. Built-in IPS and IDS on each port ensures anomaly detection and attacks, allowing for an effective increase in security.



The system equipped with a high-performance profiler passively builds wide visibility of your infrastructure, based on data flowing through the platform. The platform is compatible with leading IDS and SIEM systems, which allows for easy implementation in a monitored environment.

Benefits

- 1 Automated data flow monitoring and anomaly control on Dynacon switches.
- 2 Detailed visibility based on a deep analytics profiler
- 3 The system is equipped with API and SDN tools
- 4 Aggregation of correlator and preprocessor functions
- 5 Local analytics and data storage
- 6 Simplified license with the option of purchasing it for subsequent periods

The system equipped with a high-performance profiler passively builds wide visibility of your infrastructure based on the data flowing through the platform.

The enormous performance of specialized processors allows for effective work in a hybrid communication environment while ensuring network security and monitoring in real time.

Hardware acceleration for encryption and compression – QAT. Unprecedented controller performance (depending on the module) ensured up to 400 Gb/s for symmetric keys, up to 100 K Ops/s for public keys and up to 160 Gb/s compression.

Command-line management is flexible and easy for any network engineer, however, to manage multiple firewalls that protect your network in ZBFW mode, you can use a dedicated central application that makes this task easier while providing information about the results of the profiler and IDS/IPS system

The built-in rule mechanism, Traceability class, allows for an innovative way to monitor virtually every parameter sent over the network and activate an alarm when the minimum and maximum values are exceeded. The traceability system coupled with a profiler provides an efficient tool for monitoring anomalies and distortions in the operating parameters of your OT and IT environment.

Parameter\ Model	4012-1	4012-2	4012-3
RAM	Up to 64 GB or 32 GB ECC	Up to 64 GB or 32 GB ECC	Up to 64 GB or 32 GB ECC
Storage	Up to 4 TB	Up to 4 TB	Up to 4 TB
Built-in ports	14 x 1 Gb/s RJ 45 (7 pair ports of ByPass) + 1 x RJ 45 shared with IO 2 x 10 Gb/s SFP+	8 x 1 Gb/s RJ 45	8 x 1 Gb/s RJ 45 (3 pairs of ByPass ports) 2 x 10 Gb/s SFP+
Dimensions	1 U W 438 mm x D 431 mm x H 44 mm	1 U W 438 mm x D 431 mm x H 44 mm	1 U W 438 mm x D 431 mm x H 44 mm
Installation	railway RACK 19"	railway RACK 19"	railway RACK 19"
Modul slots number	1	1	1
Maximum number of ports	25	16	18
Console	1 x RJ45	1 x RJ45	1 x RJ45
Watchdog	YES	YES	YES
Internal RTC	YES	YES	YES
TPM	YES (optional)	YES (optional)	YES (optional)
Power supply	300 W + 1 (in total 600 W)	300 W + 1 (in total 600 W)	300 W + 1 (in total 600 W)
Ventilation	Active - 2 fans	Active - 2 fans	Active - 2 fans
Input voltage of power supplies	AC 100V~240V @47~63Hz	AC 100V~240V @47~63Hz	AC 100V~240V @47~63Hz
Certificates	CE/FCC Class A, UL	CE/FCC Class A, UL	CE/FCC Class A, UL
Compliance	IEC 62443	IEC 62443	IEC 62443

www.dynacon.pl
Phone +48 71 307 51 73
E-mail: biuro@dynacon.pl